



# Wausau Coated Products, Inc.

Facestock Specification

60# Semi Gloss

## **FACESTOCK DESCRIPTION: 60# SEMI GLOSS**

High quality facestock with a smooth surface and a medium gloss level. Features excellent runnability and color reproduction. Has good opacity and high brightness, and is suitable for water-based and UV flexographic, UV letterpress, and offset printing applications. Contains archival properties...elemental chlorine free, non-ozone depleting and lignin free with an alkaline pH level.

Basis Weight (25 x 38 / 500) lbs.	60
Caliper, mils	3.0
Brightness, %	90
Opacity, %	91
Gloss, %	71
Smoothness, PPS, F/W	0.79/0.72
Tear, g, MD / CD	30 / 30
Tensile, lbs., MD / CD	35 / 17
pH	Alkaline
Regulatory Compliances	Indirect Food 21 CFR 176.170, 21 CFR 176.180, ASTM F963-96a Toy Safety, California Proposition 65, CONEG, RoHS, REACH, non-ozone depleting, elemental chlorine free and lignin free

*All product specifications are for informational use only. Each customer and/or end user should determine the suitability of any product for their particular application. The above specifications are based on typical values and most current information. Specific products listed were current at the time of publication, however, all raw materials are subject to change.*

Shelf Life: One year when stored at 72°F / 50% RH.

July 2010