



# Wausau Coated Products, Inc.

## Product Specification

### PCT-244

#### **ADHESIVE DESCRIPTION: PCT-244**

PCT-244 is formulated for reduced initial tack but designed for good adhesion to a variety of substrates. Adhesion to rigid plastics, films, glass, and painted metals is good. Exhibits short term removability and some long term removability depending upon the substrate. Cuts and die-cuts cleanly. Good choice for sheeted and roll-to-sheet applications.

Type	Cold Temperature Permanent
Classification	Emulsion Acrylic
pH	Alkaline
Minimum Application Temp.	+35°F
Service Temperature Range	-10°F to +250°F
Regulatory Compliances	Acute Oral Toxicity 16 CFR 1500.3, Primary Skin Irritant 16 CFR 1500.41, Primary Eye Irritant 16 CFR 1500.42, Indirect Food 21 CFR 175.105, ASTM F963-96a Toy Safety, CONEG, CPSIA, RoHS REACH and Natural Rubber Latex Free

*All product specifications are for informational use only. Each customer and/or end user should determine the suitability of any product for their particular application. The above specifications are based on typical values and most current information. Specific products listed were current at the time of publication, however, all raw materials are subject to change.*

Shelf Life: One year when stored at 72°F / 50% RH.

March 2010