



Wausau Coated Products, Inc.

Facestock Specification

2 mil Clear Polypropylene Optimized for HP Indigo Presses

FACESTOCK DESCRIPTION: 2 MIL CLEAR POLYPROPYLENE OPTIMIZED FOR HP INDIGO PRESSES

Biaxially oriented polypropylene, non-cavitated film with a "no label" look (when manufactured with a clear adhesive). This film has high machine direction stiffness and tensile strength, which produces excellent matrix stripping and high speed label dispensing properties. This film is top coated and optimized for HP Indigo Presses.

Caliper, mils	2.0
Yield, in2/lb.	15,100
Tensile, lbs/in ² , MD / TD	30,500 / 24,500
Elongation at break, % MD / TD	85 / 105
Gloss, Gardner (45°), %	90
Haze, wide angle	<3.5%
Dimensional Stability, MD/TD, % 60 Seconds at 248°	3.0 / 0
Regulatory Compliances	CONEG, Toy Safety - ASTM F963 and HP indigo Certified

All product specifications are for informational use only. Each customer and/or end user should determine the suitability of any product for their particular application. The above specifications are based on typical values and most current information. Specific products listed were current at the time of publication, however, all raw materials are subject to change.

Shelf Life: Six months when stored at 72°F / 50% RH.

February 2009