



# Wausau Coated Products, Inc.

## Facestock Specification 2 mil TC Clear Polypropylene

### **FACESTOCK DESCRIPTION: 2 MIL TC CLEAR POLYPROPYLENE**

A biaxially oriented, optically clear top coated polypropylene film with excellent clarity to produce a "no label" look when used with an appropriate adhesive. Features excellent hot/cold moisture resistance and performs well for semi-squeezable applications, but has high stiffness for good conversion and automatic dispensing. Top coated for excellent printability and is suitable for flexographic, gravure, and letterpress printing applications. Please consult your ink supplier for specific recommendations.

Caliper, mils	2.0
Yield, sq. in./lb.	15,100
Tensile Strength, lbs./in <sup>2</sup> ., MD/TD	29,000 / 26,000
Elongation at Break, %, MD / TD	105 / 120
Gloss, Gardner (45°), %	90
Dim. Stab. 60 sec at 248°F, MD / TD, %	3 / 0
Regulatory Compliances	CONEG, Heavy Metals, and is non-ozone depleting.

*All product specifications are for informational use only. Each customer and/or end user should determine the suitability of any product for their particular application. The above specifications are based on typical values and most current information. Specific product listed were current at the time of publication, however, all raw materials are subject to change.*

Shelf Life: One year when stored at 72°F / 50% RH.

February 2009

