



Wausau Coated Products, Inc.

Facestock Specification

2.3 mil White Polypropylene Optimized for HP Indigo Presses

FACESTOCK DESCRIPTION: 2.3 MIL WHITE POLYPROPYLENE OPTIMIZED FOR HP INDIGO PRESSES

Biaxially oriented polypropylene, non-cavitated film optimized for HP Indigo Presses featuring high opacity and gloss. High stiffness makes this film excellent for converting and automatic dispensing. This film also features excellent hot/cold moisture resistance and is recyclable with other polyolefin materials.

Caliper, mils	2.3
Yield, sq. in./lb.	12,200
Tensile Strength, psi, MD / TD	23,900 / 21,000
Elongation at Break, %, MD / TD	95 / 115
Gloss, Gardner (45°), %	80
Dimensional Stability, MD/TD, % 60 Seconds at 248°	3.0 / 0
Regulatory Compliances	CONEG, Toy Safety - ASTM F963 and HP indigo Certified

All product specifications are for informational use only. Each customer and/or end user should determine the suitability of any product for their particular application. The above specifications are based on typical values and most current information. Specific products listed were current at the time of publication, however, all raw materials are subject to change.

Shelf Life: Six months when stored at 72°F / 50% RH.

February 2009