



# Wausau Coated Products, Inc.

## Facestock Specification

### 2.6 mil TC Glossy White Polypropylene

#### **FACESTOCK DESCRIPTION: 2.6 MIL TC GLOSSY WHITE POLYPROPYLENE**

A glossy white polypropylene film top coated for optimum ink adhesion for flexographic, gravure (solvent, water, and UV), rotary screen, UV letterpress, and thermal transfer printing. Biaxially oriented with a high gloss surface, excellent hot/cold moisture resistance, high stiffness for conversion and automatic dispensing, and excellent die cutting performance.

Caliper, mils	2.7
Yield, sq. in./lb.	14,300
Opacity, %	88
Tensile Strength, lbs./in., MD/CD	35 / 74
Elongation at Break, %	200 / 50
Gloss, Gardner (45°), %	68
Stiffness, Gurley, MD/TD, mg	24 / 41
Dimensional Stability, MD/TD, %	-5.0 / -5.0
Regulatory Compliances	CONEG, ASTM 963a Child Toy Safety, REACH, RoHS, CPSIA, Title IV ozone depleting, and California Proposition 65

*All product specifications are for informational use only. Each customer and/or end user should determine the suitability of any product for their particular application. The above specifications are based on typical values and most current information. Specific products listed were current at the time of publication, however, all raw materials are subject to change.*

Shelf Life: One year when stored at 72°F / 50% RH.

June 2009