



Wausau Coated Products, Inc.

Facestock Specification 2.6 mil White Polypropylene

FACESTOCK DESCRIPTION: 2.6 MIL WHITE POLYPROPYLENE

A print treated white polypropylene film with excellent ink adhesion and print quality. It is very durable with high opacity and is biaxially oriented with good stiffness for conversion and automatic label dispensing. It is suitable for water-based and solvent-based flexo and gravure, UV flexo, UV letterpress, and UV screen ink printing systems. Also suitable for hot stamping systems.

Caliper, mils	2.6
Yield, sq. in./lb.	15,000
Opacity, %	88
Gloss (45°), %	70
Tensile Strength, psi MD / TD	13,100 / 27,700
Tensile Elongation, %, MD / TD	200 / 50
Stiffness, Gurley, mgf, MD / TD	22 / 42
Dimensional Stability, %, MD / TD	-5.0 / -5.0
Regulatory Compliances	CONEG, ASTM 963a Child Toy Safety, REACH, RoHS, CPSIA, Title IV ozone depleting, and California Proposition 65

All product specifications are for informational use only. Each customer and/or end user should determine the suitability of any product for their particular application. The above specifications are based on typical values and most current information. Specific products listed were current at the time of publication, however, all raw materials are subject to change.

Shelf Life: One year when stored at 72°F / 50% RH.

March 2009

