



Wausau Coated Products, Inc.

Facestock Specification

3 mil TC Matte White Polypropylene

FACESTOCK DESCRIPTION: 3 MIL TC MATTE WHITE POLYPROPYLENE

A biaxially oriented, matte polypropylene designed for thermal transfer printing. Abrasion and weather resistant. Features good barcode scanability and is compatible with a wide range of thermal transfer ribbons. Also suitable for water-based and solvent-based flexographic, gravure, and screen printing applications.

Caliper, mils	3
Yield, sq. in./lb.	13,100
Opacity, %	90
Tensile Strength, psi, MD/TD	12,300 / 23,300
Elongation at Break, %	200 / 53
Stiffness, Gurley, mgf, MD / TD	29 / 40
Dimensional Stability @ 275°F, MD / TD	-5.0 / -5.0
Regulatory Compliances	CONEG, ASTM 963a Child Toy Safety, REACH, RoHS, CPSIA, Title IV ozone depleting, and California Proposition 65

All product specifications are for informational use only. Each customer and/or end user should determine the suitability of any product for their particular application. The above specifications are based on typical values and most current information. Specific products listed were current at the time of publication, however, all raw materials are subject to change.

Shelf Life: One year when stored at 72°F / 50% RH.

March 2009