



Wausau Coated Products, Inc.

Adhesive Specification

R-2150+

ADHESIVE DESCRIPTION: R-2150+

An excellent removable adhesive with low to moderate adhesion on most surfaces, R-2150+ is a good choice for a variety of removable applications. It functions most effectively on smooth surfaces, including glass, paper and painted metal. It has excellent stability and demonstrates very little growth in adhesion over time however, adhesion growth will vary depending upon substrate. Pretesting is recommended to determine end-use applicability.

| | |
|---------------------------|---|
| Type | Ultra-Removable |
| Classification | Emulsion Acrylic |
| pH | Neutral to Slightly Alkaline |
| Minimum Application Temp. | -10°F |
| Service Temperature Range | -40°F to +160°F |
| Regulatory Compliances | Acute Oral Toxicity 16 CFR 1500.3, Primary Skin Irritant 16 CFR 1500.41, Primary Eye Irritant 16 CFR 1500.42, Indirect Food 21 CFR 175.105, ASTM F963-96a Toy Safety, CONEG, and RoHS |

All product specifications are for informational use only. Each customer and/or end user should determine the suitability of any product for their particular application. The above specifications are based on typical values and most current information. Specific products listed were current at the time of publication, however, all raw materials are subject to change.

Shelf Life: One year when stored at 72°F / 50% RH.

March 2010