



Wausau Coated Products, Inc.

Facestock Specification

60# Semi Gloss with 10% PCW

FACESTOCK DESCRIPTION: 60# SEMI GLOSS WITH 10% PCW

Bright white facestock with a medium gloss level featuring 10% post consumer waste. Has high opacity and a smooth finish suitable for water-based and UV flexographic, UV letterpress, and offset printing applications. This premium printing paper is FSC certified and elemental chlorine free (EFC).



Basis Weight (25 x 38 / 500) lbs.	60
Caliper, mils	2.85
Brightness, %	92
Opacity, %	91
Gloss	72
Smoothness, PPS	1.0-1.1
Tear, g, MD / CD	31 / 35
Tensile, lbs., MD / CD	27 / 15
pH	Alkaline
Recycled Content, %	10
PCW, %	10
Regulatory Compliances	FDA 21 CFR 176.170 for indirect food contact, CONEG, Heavy Metals, ASTM F963-96a Child Toy Safety, Federal Hazardous Substances Act 16 CFR, Part 1500.3 Acute Oral Toxicity, Part 1500.42 Primary Eye Irritant, Part 1500.41 Primary Skin Irritant legislation, RoHS, Non-ozone depleting, lignin free, elemental chlorine free & FSC certified

All product specifications are for informational use only. Each customer and/or end user should determine the suitability of any product for their particular application. The above specifications are based on typical values and most current information. Specific products listed were current at the time of publication, however, all raw materials are subject to change.

Shelf Life: One year when stored at 72°F / 50% RH.

February 2009