



# Wausau Coated Products, Inc.

Product Specification #W000017  
55# Semi Gloss / PCT-425 / 40# SC

## **FACESTOCK DESCRIPTION: 55# SEMI GLOSS**

Medium gloss, good opacity and brightness with a smooth finish suitable for water-based and UV flexographic, and UV letterpress applications. Extremely wickproof. An excellent choice for beverage label applications including milk, water, and juice bottles.

Basis Weight (25 x 38 / 500) lbs.	55
Caliper, mils	2.8
Tensile, lbs., MD / CD	30 / 18
Tear, g, MD / CD	40 / 44
Brightness, %	86
Opacity, %	86.5
Gloss	70
Regulatory Compliances	FDA 21 CFR 175.105 for incidental food contact, CONEG, Heavy Metals, ASTM F963a Child Toy Safety, California Prop. 65, and NAFTA.

## **ADHESIVE DESCRIPTION: PCT-425**

Very aggressive cold temperature permanent which exhibits excellent adhesion to films, even in the presence of moisture and/or frost. Excellent choice for dairy label applications.

Type	Cold Temperature Permanent
Classification	Rubber Based
Regulatory Compliances	FDA 21 CFR 175.105 for incidental food contact, CONEG, Heavy Metals, ASTM F963a Child Toy Safety, and NAFTA.
Minimum Application Temp.	+35°F
Service Temperature Range	-15°F to +140°F

## **LINER DESCRIPTION: 40# SC LINER**

A supercalendered bleached kraft liner. Superior die-cutting and stripping properties. Recommended for roll-to-roll applications. Good back printability.

Basis Weight (25 x 38 / 500) lbs.	44.8
Caliper, mils	2.5
Brightness, %	81
Opacity, %	65
Tensile, lbs./in., MD / CD	34 / 22
Tear, G, MD / CD	32 / 34
Gloss, 75°	45
Regulatory Compliances	FDA 21 CFR 175.105 for incidental food contact, California Clean Water (Prop. 65), and NAFTA. Lignin free.

*All product specifications are for informational use only. Each customer and/or end user should determine the suitability of any product for their particular application. The above specifications are based on typical values and most current information.*

Shelf Life: One year when stored at 72°F / 50% RH.