



Wausau Coated Products, Inc.

Product Specification #W005252

60# Matte Litho Optimized for Use on HP Indigo Presses / PCT-2242 / 40# SC

FACESTOCK DESCRIPTION: 60# MATTE LITHO OPTIMIZED FOR USE ON HP INDIGO DIGITAL PRESSES

A bright white matte litho with a high quality smooth surface yielding consistent press performance where inks dry fast. Optimized for use on HP Indigo Digital Printing Systems. Contains archival properties ... elemental chlorine-free and lignin free with an alkaline pH level. Also suitable for offset printing.

Basis Weight (25 x 38 / 500) lbs.	60
Caliper, mils	3.6
Brightness, %	92
Opacity, %	92
Gloss, 60°	30
pH	Alkaline
Regulatory Compliances	Elemental chlorine-free and lignin free

ADHESIVE DESCRIPTION: PCT-2242

A cold temperature emulsion acrylic permanent which exhibits moderate initial tack to a variety of substrates. Adhesion to rigid plastics, film, glass, and painted metals is good. Die-cuts cleanly. Designed for laser applications and is a good choice for roll-to-sheet applications.

Type	Cold Temperature Permanent
Classification	Emulsion Acrylic
Regulatory Compliances	FDA 21 CFR 175.105 for incidental food contact, CONEG, Heavy Metals, ASTM 963a Child Toy Safety, Acute Oral Toxicity, Primary Dermal Irritant, Primary Eye Irritant, and NAFTA.
pH	Alkaline
Minimum Application Temp.	+35°F
Service Temperature Range	-10°F to +200°F

LINER DESCRIPTION: 40# SC LINER

A supercalendered bleached kraft liner. Superior die-cutting and stripping properties. Recommended for roll-to-roll applications. Good back printability.

Basis Weight (25 x 38 / 500) lbs.	44.8
Caliper, mils	2.5
Brightness, %	81
Opacity, %	65
Tensile, lbs./in., MD / CD	34 / 22
Tear, G, MD / CD	32 / 34
Gloss, 75°	45
Regulatory Compliances	FDA 21 CFR 175.105 for incidental food contact, California Clean Water (Prop. 65), and NAFTA. Lignin free.

All product specifications are for informational use only. Each customer and/or end user should determine the suitability of any product for their particular application. The above specifications are based on typical values and most current information.

Shelf Life: One year when stored at 72°F / 50% RH.

06D