



Wausau Coated Products, Inc.

Product Specification #W006811

60# High Gloss / PCT-241 / 40#

FACESTOCK DESCRIPTION: 60# HIGH GLOSS

A blue-white shade and mirror-smooth finish with excellent ink receptivity. Suitable for letterpress, offset, gravure, and water and UV flexographic printing applications.

Basis Weight (25 x 38 / 500) lbs.	59.4
Caliper, mils	3.5
Tensile, lbs., MD / CD	39 / 18
Tear, g, MD / CD	41 / 42
Brightness, %	83
Opacity, %	93

ADHESIVE DESCRIPTION: PCT-241

Cold temperature emulsion acrylic permanent which exhibits high initial tack and very good adhesion to a variety of substrates including corrugated, rigid plastics, films, glass, and painted metal substrates. It offers good die-cutting and stripping characteristics. It is not recommended for water immersion.

Type	Cold Temperature Permanent
Classification	Emulsion Acrylic
Regulatory Compliances	FDA 21 CFR 175.105 for incidental food contact, CONEG, Heavy Metals, ASTM F963a Child Toy Safety, Acute Oral Toxicity, Primary Dermal Irritant, Primary Eye Irritant, and NAFTA
pH	Alkaline
Minimum Application Temp.	+25°F
Service Temperature Range	-10°F to +200°F

LINER DESCRIPTION: 40# SC LINER

A supercalendered bleached kraft liner. Superior die-cutting and stripping properties. Recommended for roll-to-roll applications. Good back printability.

Basis Weight (25 x 38 / 500) lbs.	45.6
Caliper, mils	2.5
Tensile, lbs./in., MD / CD	41 / 20
Tear, G, MD / CD	36 / 40
Gloss, 75°	57

All product specifications are for informational use only. Each customer and/or end user should determine the suitability of any product for their particular application. The above specifications are based on typical values and most current information.

Shelf Life: One year when stored at 72°F / 50% RH.