



Wausau Coated Products, Inc.

Product Specification #W007353
60# High Gloss / P-872 / 40# SC

FACESTOCK DESCRIPTION: 60# HIGH GLOSS

A blue-white shade and mirror-smooth finish with excellent ink receptivity. Suitable for letterpress, offset, gravure, and water and UV flexographic printing applications.

| | |
|-----------------------------------|---------|
| Basis Weight (25 x 38 / 500) lbs. | 59.4 |
| Caliper, mils | 3.5 |
| Tensile, lbs., MD / CD | 39 / 18 |
| Tear, g, MD / CD | 41 / 42 |
| Brightness, % | 83 |
| Opacity, % | 93 |

ADHESIVE DESCRIPTION: P-872

A highly aggressive rubber based permanent adhesive which exhibits superior adhesion to a variety of substrates, particularly recycled corrugated and films. It offers good die-cutting and stripping characteristics. Pretesting is recommended to determine suitability for a particular end-use application.

| | |
|---------------------------|---|
| Type | General Purpose Permanent |
| Classification | Rubber Based |
| Regulatory Compliances | FDA 21 CFR 175.105 for incidental food contact, CONEG, Heavy Metals, ASTM F963a Child Toy Safety, California Clean Water (Prop. 65), and NAFTA. |
| Minimum Application Temp. | +35°F |
| Service Temperature Range | -5°F to +200°F |

LINER DESCRIPTION: 40# SC LINER

A supercalendered bleached kraft liner. Superior die-cutting and stripping properties. Recommended for roll-to-roll applications. Good back printability.

| | |
|-----------------------------------|---------|
| Basis Weight (25 x 38 / 500) lbs. | 45.6 |
| Caliper, mils | 2.5 |
| Tensile, lbs./in., MD / CD | 41 / 20 |
| Gloss, 75° | 57 |

All product specifications are for informational use only. Each customer and/or end user should determine the suitability of any product for their particular application. The above specifications are based on typical values and most current information.

Shelf Life: One year when stored at 72°F / 50% RH.