



# Wausau Coated Products, Inc.

Product Specification #W007466

56# Bright Silver Metalized Paper Optimized for HP Indigo Printing / 245 / 44#PK

### **FACESTOCK DESCRIPTION: 56# BRIGHT SILVER METALIZED PAPER OPTIMIZED FOR HP INDIGO**

A smooth, bright silver metalized paper with the appearance of foil. Has superior converting properties and is suitable for flexographic, offset, and gravure printing applications; engineered specifically to run on HP Indigo Digital Printing Systems.

Basis Weight (25 x 38 / 500) lbs.	56.1
Caliper, mils	2.7
Tensile, lbs., MD / CD	28 / 18
Tear, g, MD / CD	43 / 48
Stiffness, mg, (Gurley), MD/ CD	80 / 52
Regulatory Compliances	Lignin free

### **ADHESIVE DESCRIPTION: PCT-245**

A cold temperature emulsion acrylic permanent which exhibits good initial tack and good adhesion to a variety of substrates including corrugated, rigid plastics, films, glass, and painted metal surfaces. It offers excellent die-cutting and stripping characteristics. Designed for face and back label use and remains affixed when immersed in an ice bucket. It also features short term repositionability on bottles.

Type	Cold Temperature Permanent
Classification	Emulsion Acrylic
Regulatory Compliances	FDA 21 CFR 175.105 for incidental food contact, CONEG, Heavy Metals, ASTM 963a Child Toy Safety, Acute Oral Toxicity, Primary Dermal Irritant, Primary Eye Irritant, and NAFTA.
pH	Alkaline
Minimum Application Temp.	+25°F
Service Temperature Range	-10°F to +200°F

### **LINER DESCRIPTION: 44# PK**

A polycoated brown kraft liner with superior die-cutting and stripping properties. Designed for high-speed label dispensing and is recommended for roll-to-roll applications.

Basis Weight (25 x 38 / 500) lbs.	44# +/- 10%
Caliper, mils	3.2 +/- 10%

*All product specifications are for informational use only. Each customer and/or end user should determine the suitability of any product for their particular application. The above specifications are based on typical values and most current information*

Shelf Life: One year when stored at 72°F / 50% RH.

07D