



Wausau Coated Products, Inc.

Product Specification #W007850

60# High Gloss optimized for use on HP Indigo presses / PCT-245 / 44#PK

FACESTOCK DESCRIPTION: 60# HIGH GLOSS OPTIMIZED FOR USE ON HP INDIGO PRESSES

A blue-white glossy, shade and mirror-smooth finish engineered to run specifically on HP Indigo Digital Printing Systems. Features high quality color reproduction.

| | |
|-----------------------------------|--|
| Basis Weight (25 x 38 / 500) lbs. | 60.0 |
| Caliper, mils | 4.0 |
| Tensile, lbs., MD / CD | 26 / 16 |
| Tear, g, MD / CD | 49 / 51 |
| Opacity, % | 90.0 |
| Regulatory Compliances | FDA 21 CFR 175.105 for incidental food contact, CONEG, ASTM F963-96a Child Toy Safety, Prop. 65, and NAFTA. Free of natural latex. |

ADHESIVE DESCRIPTION: PCT-245

A cold temperature emulsion acrylic permanent which exhibits good initial tack and good adhesion to a variety of substrates including corrugated, rigid plastics, films, glass, and painted metal surfaces. It offers excellent die-cutting and stripping characteristics. Designed for face and back label use and remains affixed when immersed in an ice bucket. It also features short term repositionability on bottles.

| | |
|---------------------------|---|
| Type | Cold Temperature Permanent |
| Classification | Emulsion Acrylic |
| Regulatory Compliances | FDA 21 CFR 175.105 for incidental food contact, CONEG, Heavy Metals, ASTM 963a Child Toy Safety, Acute Oral Toxicity, Primary Dermal Irritant, Primary Eye Irritant, and NAFTA. |
| pH | Alkaline |
| Minimum Application Temp. | +25°F |
| Service Temperature Range | -10°F to +200°F |

LINER DESCRIPTION: 44# PK

A polycoated brown kraft liner with superior die-cutting and stripping properties. Designed for high-speed label dispensing and is recommended for roll-to-roll applications.

| | |
|-----------------------------------|-------------|
| Basis Weight (25 x 38 / 500) lbs. | 44# +/- 10% |
| Caliper, mils | 3.2 +/- 10% |

All product specifications are for informational use only. Each customer and/or end user should determine the suitability of any product for their particular application. The above specifications are based on typical values and most current information.

Shelf Life: One year when stored at 72°F / 50% RH.

07H