



Wausau Coated Products, Inc.

Product Specification W007882

100% PCW Recycled Laser/Ink Jet / PCT-242 / 52# Laser

FACESTOCK DESCRIPTION: 100% PCW RECYCLED LASER / INKJET

Recycled facestock made with 100% recycled post-consumer fiber and processed chlorine free (PCF). It has Forest Stewardship Council (FSC) and Green Seal certification. It is acid free and lignin free and is guaranteed for inkjet, laser, copier and offset printing applications. With a 92% brightness, it is one of the whitest recycled facestocks on the market today.



Basis Weight (25 x 38 / 500) lbs.	50
Caliper, mils	4
Brightness, %	92
Opacity, %	87
Smoothness. Sheffield	220
Tear, g, MD / CD	48 / 48
pH	Acid Free
Recycled Content, %	100
PCW, %	100
Regulatory Compliances	ASTM F963-03 Toy Safety, California Proposition 65, CONEG, RoHS, FSC, Green Seal Certified, Acid Free, Lignin Free and Processed Chlorine Free

ADHESIVE DESCRIPTION: PCT-242

A cold temperature emulsion acrylic permanent which exhibits good initial tack to a variety of substrates. Adhesion to rigid plastics, film, glass, and painted metals is good. Die-cuts cleanly. Designed for laser applications and is a good choice for roll-to-sheet applications.

Type	Cold Temperature Permanent
Classification	Emulsion Acrylic
pH	Alkaline
Minimum Application Temp.	+35°F
Service Temperature Range	-10°F to +200°F
Regulatory Compliances	Acute Oral Toxicity 16 CFR 1500.3, Primary Skin Irritant 16 CFR 1500.41, Primary Eye Irritant 16 CFR 1500.42, Indirect Food 21 CFR 175.105, California Proposition 65, CONEG, & REACH

LINER DESCRIPTION: 52# LASER

A supercalendered bleached kraft liner specially designed for sheeted applications and well suited for laser printing. Features excellent dimensional stability. Recommended for roll-to-sheet applications.

Basis Weight (25 x 38 / 500) lbs.	55
Caliper, mils	3.5
Brightness, %	81.5
Opacity, %	87
Smoothness 5S,PPS	2.2
Tear, G, MD / CD	50 / 60
Tensile, lbs./in., MD / CD	35 / 15
Regulatory Compliances	REACH, CONEG, ASTM F963-03 Toy Safety, and RoHS

All product specifications are for informational use only. Each customer and/or end user should determine the suitability of any product for their particular application. The above specifications are based on typical values and most current information. Specific products listed were current at the time of publication, however, all raw materials are subject to change.

Shelf Life: One year when stored at 72°F / 50% RH.

August 2011