



Wausau Coated Products, Inc.

Product Specification #W008010

60# Matte Litho Optimized for use on HP Indigo Digital Presses / PCT-245 / 44# PK

FACESTOCK DESCRIPTION: 60# MATTE LITHO OPTIMIZED FOR USE ON HP INDIGO DIGITAL PRESSES

A bright white, opaque matte sheet with a smooth surface and a reduced gloss level suitable. Optimized for use on HP Indigo Digital Printing Systems.

Basis Weight (25 x 38 / 500) lbs.	60.0
Caliper, mils	3.6
Tensile, lbs./in., MD / CD	36 / 14
Tear, g, MD / CD	46 / 53

ADHESIVE DESCRIPTION: PCT-245

A cold temperature emulsion acrylic permanent which exhibits good initial tack and good adhesion to a variety of substrates including corrugated, rigid plastics, films, glass, and painted metal surfaces. It offers excellent die-cutting and stripping characteristics. Designed for face and back label use and remains affixed when immersed in an ice bucket. It also features short term repositionability on bottles.

Type	Cold Temperature Permanent
Classification	Emulsion Acrylic
Regulatory Compliances	FDA 21 CFR 175.105 for incidental food contact, CONEG, Heavy Metals, ASTM 963a Child Toy Safety, Acute Oral Toxicity, Primary Dermal Irritant, Primary Eye Irritant, and NAFTA.
pH	Alkaline
Minimum Application Temp.	+25°F
Service Temperature Range	-10°F to +200°F

LINER DESCRIPTION: 44# PK

A polycoated brown kraft liner with superior die-cutting and stripping properties. Designed for high-speed label dispensing and is recommended for roll-to-roll applications.

Basis Weight (25 x 38 / 500) lbs.	44# +/- 10%
Caliper, mils	3.2 +/- 10%

All product specifications are for informational use only. Each customer and/or end user should determine the suitability of any product for their particular application. The above specifications are based on typical values and most current information.

Shelf Life: One year when stored at 72°F / 50% RH.

07H