



Wausau Coated Products, Inc.

Product Specification W008260

60# Recycled Vellum with 100% PCW Optimized for HP Indigo Presses / PCT-245 / 44# PK

FACESTOCK DESCRIPTION: 60# RECYCLED VELLUM WITH 100% PCW OPTIMIZED FOR HP INDIGO PRESSES

100% Recycled Vellum is the perfect "green" choice. This facestock uses the highest quality recycled fiber available to produce one of the brightest and whitest vellum facestocks made with 100% post-consumer fiber. It is manufactured with "wet strength" properties to increase performance in moist environments. Excellent for high speed packaging lines and is a great stock for premium and eco-friendly labeling such as wine bottles, gourmet food, and beverages. Top coated and optimized for HP Indigo Presses. It is FSC certified.

Basis Weight (25 x 38 / 500) lbs.	60
Caliper, mils	4.5
GSM	88.8
Brightness, %	95
Opacity, %	90
Smoothness, Sheffield	150
Tear, g, MD/CD	60 / 72
Tensile, lbs./in., MD/CD	38 / 18
pH	Alkaline
Recycled Content, %	100
PCW, %	100
Regulatory Compliances	FSC & Rainforest Alliance Certified, California Proposition 65, Heavy Metals, and processed chlorine free

ADHESIVE DESCRIPTION: PCT-245

A cold temperature emulsion acrylic permanent which exhibits good initial tack and good adhesion to a variety of substrates including corrugated, rigid plastics, films, glass, and painted metal surfaces. It offers excellent die-cutting and stripping characteristics. Designed for face and back label use and remains affixed when immersed in an ice bucket. It also features short term repositionability on bottles.

Type	Cold Temperature Permanent
Classification	Emulsion Acrylic
pH	Alkaline
Minimum Application Temp.	+25°F
Service Temperature Range	-10°F to +200°F
Regulatory Compliances	FDA 21 CFR 175.105 for incidental food contact, CONEG, Heavy Metals, ASTM 963a Child Toy Safety, Acute Oral Toxicity, Primary Dermal Irritant, Primary Eye Irritant, and NAFTA

LINER DESCRIPTION: 44# PK

A polycoated brown kraft liner with superior die-cutting and stripping properties. Designed for high-speed label dispensing and is recommended for roll-to-roll applications.

Basis Weight (25 x 38 / 500) lbs.	44# +/- 10%
Caliper, mils	3.2 +/- 10%

All product specifications are for informational use only. Each customer and/or end user should determine the suitability of any product for their particular application. The above specifications are based on typical values and most current information. Specific products listed were current at the time of publication, however, all raw materials are subject to change.

Shelf Life: One year when stored at 72°F / 50% RH.

February 2009