



Wausau Coated Products, Inc.

Product Specification W008472

70# Recycled Matte with 100% PCW Optimized for HP Indigo Presses / PCT-245 / 44# PK

FACESTOCK DESCRIPTION: 70# RECYCLED MATTE WITH 100% PCW OPTIMIZED FOR HP INDIGO PRESSES

70# high opacity paper with a matte finish and 84 brightness level. Featuring 100% recycled and 100% post consumer content. Top coated and optimized for HP Indigo Presses. This sheet delivers a beautiful print surface and unique environmental features.

Basis Weight (25 x 38 / 500) lbs.	70
Caliper, mils	4.1
GSM	103.5
Brightness, %	84
Opacity, %	97
pH	Acid Free
Recycled Content, %	100
PCW, %	100
Regulatory Compliance	Green-e, Ancient Forest Friendly, Wind Generated Electricity, acid free and archival

ADHESIVE DESCRIPTION: PCT-245

A cold temperature emulsion acrylic permanent which exhibits good initial tack and good adhesion to a variety of substrates including corrugated, rigid plastics, films, glass, and painted metal surfaces. It offers excellent die-cutting and stripping characteristics. Designed for face and back label use and remains affixed when immersed in an ice bucket. It also features short term repositionability on bottles.

Type	Cold Temperature Permanent
Classification	Emulsion Acrylic
pH	Alkaline
Minimum Application Temp.	+25°F
Service Temperature Range	-10°F to +200°F
Regulatory Compliances	FDA 21 CFR 175.105 for incidental food contact, CONEG, Heavy Metals, ASTM 963a Child Toy Safety, Acute Oral Toxicity, Primary Dermal Irritant, Primary Eye Irritant, and NAFTA.

LINER DESCRIPTION: 44# PK

A polycoated brown kraft liner with superior die-cutting and stripping properties. Designed for high-speed label dispensing and is recommended for roll-to-roll applications.

Basis Weight (25 x 38 / 500) lbs.	44# +/- 10%
Caliper, mils	3.2 +/- 10%

All product specifications are for informational use only. Each customer and/or end user should determine the suitability of any product for their particular application. The above specifications are based on typical values and most current information. Specific products listed were current at the time of publication, however, all raw materials are subject to change.

Shelf Life: One year when stored at 72°F / 50% RH.

February 2009