



# Wausau Coated Products, Inc.

## Product Specification W008472

### 70# Recycled Matte with 100% PCW Optimized for HP Indigo Presses / PCT-245 / 44# PK

#### **FACESTOCK DESCRIPTION: 70# RECYCLED MATTE WITH 100% PCW\* OPTIMIZED FOR HP INDIGO PRESSES**

70# high opacity paper with a matte finish. Featuring 100% recycled and 100% post consumer content. Top coated and optimized for HP Indigo Presses. This sheet delivers a beautiful print surface and unique environmental features.

Basis Weight (25 x 38 / 500) lbs.	70
Caliper, mils	4.1
GSM	103.5
Brightness, %	84
Opacity, %	97
pH	Acid Free
Recycled Content, %	100
PCW, %	100
Regulatory Compliance	Green-e, Ancient Forest Friendly, and Wind Generated Electricity

\*100% post consumer according to International Standard - 50% post consumer according to US EPA

#### **ADHESIVE DESCRIPTION: PCT-245**

A cold temperature emulsion acrylic permanent which exhibits good initial tack and good adhesion to a variety of substrates including corrugated, rigid plastics, films, glass, and painted metal surfaces. It offers excellent die-cutting and stripping characteristics. Adhesive designed for face and back label use on glass bottles and remains affixed when immersed in an ice bucket. It also features short term repositionability on bottles and hot water removability depending on face, substrate, water temperature, and dwell time.

Type	Cold Temperature Permanent
Classification	Emulsion Acrylic
pH	Alkaline
Minimum Application Temp.	+25°F
Service Temperature Range	-10°F to +200°F
Regulatory Compliances	Acute Oral Toxicity 16 CFR 1500.3, Primary Skin Irritant 16 CFR 1500.41, Primary Eye Irritant 16 CFR 1500.42, Indirect Food 21 CFR 175.105, ASTM F963-96a Toy Safety, CONEG, RoHS, & REACH

#### **LINER DESCRIPTION: 44# PK**

A polycoated brown kraft liner with superior die-cutting and stripping properties. Designed for high-speed label dispensing and is recommended for roll-to-roll applications.

Basis Weight (25 x 38 / 500) lbs.	48# +/- 10%
Caliper, mils	3.2 +/- 10%
Regulatory Compliances	California Proposition 65, CONEG, RoHS and REACH

*All product specifications are for informational use only. Each customer and/or end user should determine the suitability of any product for their particular application. The above specifications are based on typical values and most current information. Specific products listed were current at the time of publication, however, all raw materials are subject to change.*

Shelf Life: One year when stored at 72°F / 50% RH.

October 2010