



Wausau Coated Products, Inc.

Product Specification W012900

63# Bright Silver Metalized Paper Optimized for HP Indigo Presses / PCT-245 / 44# PK

FACESTOCK DESCRIPTION: 63# BRIGHT SILVER METALIZED PAPER OPTIMIZED FOR HP INDIGO PRESSES

A smooth bright silver metalized paper with the appearance of foil. Has superior converting properties and is top coated and optimized for HP Indigo Presses.

| | |
|-----------------------------------|----------|
| Basis Weight (25 x 38 / 500) lbs. | 63 |
| Caliper, mils | 3.2 |
| Tensile, lbs., MD / CD | 34 / 20 |
| Tear, g, MD / CD | 48 / 48 |
| Stiffness, mg, (Gurley), MD / CD | 141 / 95 |

ADHESIVE DESCRIPTION: PCT-245

A cold temperature emulsion acrylic permanent which exhibits good initial tack and good adhesion to a variety of substrates including corrugated, rigid plastics, films, glass, and painted metal surfaces. It offers excellent die-cutting and stripping characteristics. Adhesive designed for face and back label use on glass bottles and remains affixed when immersed in an ice bucket. It also features short term repositionability on bottles and hot water removability depending on face, substrate, water temperature, and dwell time.

| | |
|---------------------------|--|
| Type | Cold Temperature Permanent |
| Classification | Emulsion Acrylic |
| pH | Alkaline |
| Minimum Application Temp. | +25°F |
| Service Temperature Range | -10°F to +200°F |
| Regulatory Compliances | Acute Oral Toxicity 16 CFR 1500.3, Primary Skin Irritant 16 CFR 1500.41, Primary Eye Irritant 16 CFR 1500.42, Indirect Food 21 CFR 175.105, ASTM F963-96a Toy Safety, CONEG, RoHS, & REACH |

LINER DESCRIPTION: 44# PK

A polycoated brown kraft liner with superior die-cutting and stripping properties. Designed for high-speed label dispensing and is recommended for roll-to-roll applications.

| | |
|-----------------------------------|--|
| Basis Weight (25 x 38 / 500) lbs. | 48# +/- 10% |
| Caliper, mils | 3.2 +/- 10% |
| Regulatory Compliances | California Proposition 65, CONEG, RoHS and REACH |

All product specifications are for informational use only. Each customer and/or end user should determine the suitability of any product for their particular application. The above specifications are based on typical values and most current information. Specific products listed were current at the time of publication, however all raw materials are subject to change.

Shelf Life: Once year when stored at 72°F / 50% RH.

September 2010