

PREMIUM STICKER MATERIAL PRODUCT BULLETIN



2.6 MIL WHITE POLYPROPYLENE SCORED AND ZERO SCORE LAYFLAT LINER

Premium 2.6 mil white polypropylene sticker product, designed to meet all your needs with unmatched durability and printability. The face stock offers exceptional print quality, available with an indigo top coat or standard topcoat to suit your specific requirements. With a permanent adhesive, this label ensures a secure and lasting bond on various surfaces. Choose between two liner options: a special 3/4" scored liner that cracks and peels effortlessly for precise application and alignment, or a thick 6 mil layflat liner that keeps your cutouts flat and gives your stickers a robust feel.

With Score

W038033 - Indigo 2.6 mil White Polypropylene / AT-2060 / 80# (3/4") SB

W038223 - 2.6 mil TC White Polypropylene / AT-2060 / 80# (3/4") SB

Without Score

W037656 - Indigo 2.6 mil White Polypropylene / AT-2060 / 6 mil Layflat

W034394 - 2.6 mil TC White Polypropylene / AT-2060 / 6 mil Layflat

For additional information and to request samples, visit our website wausaucoated.com or contact our Customer Solutions Team at **800-345-8039**.



FACESTOCK DESCRIPTION: 2.6 MIL WHITE POLYPROPYLENE (INDIGO & TC)

A glossy white polypropylene film top coated and optimized for HP Indigo Presses. Biaxially oriented, cavitated, with a high gloss surface, excellent hot/cold moisture resistance, high stiffness for conversion and automatic dispensing, and excellent die cutting performance.

Basis Weight (25 x 38 /500), lbs.	30.64
Caliper, mils	2.6

ADHESIVE DESCRIPTION: AT-2060

An aggressive all-temperature emulsion acrylic permanent adhesive with good room temperature and excellent cold temperature performance. Exhibits high initial tack and adhesion, even on most textured and hard-to-label substrates, including corrugated. Designed with good die-cutting and stripping properties.

Type	All Temperature Hybrid
Classification	Emulsion Acrylic
Minimum Application Temp °F	-20
Service Temperature Range °F	-65 to +200

LINER OPTION DESCRIPTION: 80# (3/4") SCORE BACK

Clay-coated bleached kraft liner designed for roll-to-sheet applications. Manufactured with liner scores every 3/4" apart.

Caliper, mils	4.6 mils
Opacity	93%
Tensile Strength, MD / TD, psi	36 / 23 psi
Tear, MD / TD	66 / 71 g

LINER OPTION DESCRIPTION: 6 MIL LAYFLAT

Clay-coated bleached kraft liner designed for roll-to-sheet applications. Manufactured with liner scores every 3/4" apart.

Caliper, mils	6.2 mils
Gloss, 75 °	18%
Tensile Strength, MD / TD, psi	46/19 lbs
Tear, MD / TD	90 / 108 g

Shelf life: One year when stored at 72° F / 50% RH

Note: All product specifications are for informational use only. For more details visit wausaucoated.com.