

**FACESTOCK DESCRIPTION: 60# Semi Gloss**

High quality facestock with a smooth surface and a medium gloss level. Features excellent runnability and color reproduction. Has good opacity and high brightness, and is suitable for water-based and UV flexographic, UV letterpress, and offset printing applications. Contains archival properties...elemental chlorine free, non-ozone depleting and lignin free with an alkaline pH level.

Basis Weight (25 x 38 / 500), lbs.	60
Caliper, mils	3
Brightness, %	90
Gloss, 75°, %	71
Opacity, %	91
Tear, MD / CD, g	30 / 30
Tensile, MD / CD, lbs.	35 / 17
Smoothness, PPS, F/W, units	0.79/0.72
pH	Alkaline
Regulatory Compliances	ASTM F963 Child Toy Safety, California Proposition 65, CONEG, Lignin Free, RoHS, REACH, CPSIA, Non-ozone Depleting, Elemental Chlorine Free

**ADHESIVE DESCRIPTION: PCT-524**

A very aggressive cold temperature permanent adhesive with great cold flow properties and an excellent choice for dairy label applications. PCT-524 will adhere to a frosted surface depending on the amount of frost and moisture present. Pretesting to determine end use applicability is recommended.

Type	Cold Temperature Permanent
Classification	Rubber Based
Minimum Application Temp., °F	10
Service Temperature Range, °F	-40 to +150
Regulatory Compliances	CONEG, RoHS, REACH, FDA 21 CFR 175.105, Natural Rubber Latex Free

**LINER DESCRIPTION: 40# SC**

A supercalendered bleached liner. Superior die-cutting and stripping properties. Recommended for roll-to-roll applications. Good back printability.

Basis Weight (25 x 38 / 500), lbs.	42
Caliper, mils	2.5

All product specifications are for informational use only. Each customer and/or end user should determine the suitability of any product for their particular application. The above specifications are based on typical values and most current information. Specific products listed were current at the time of publication, however, all raw materials are subject to change.

Shelf Life: One year when stored at 72°F / 50% RH.