



**FACESTOCK DESCRIPTION: Natural Kraft VersaPly™**

Strong, durable reinforced facestock that provides a rustic and “earthy” look. 100% Recycled Natural Kraft is a perfect choice for label applications that require a distinctive and all natural look. A great end use example includes shelf marking for wine, beer and spirits, organic, natural and gourmet foods. Suitable for high speed & desktop laser printing; also can be top coated for HP Indigo printing.

Basis Weight (25 x 38 / 500), lbs	80.52
Caliper, mils	7
Tear, MD / CD, g	79 / 101
Tensile, MD / CD, lbs.	29 / 11

**ADHESIVE DESCRIPTION: R-2211**

R-2211 has good initial tack and adhesion to papers. Adhesion to rigid plastics, films, glass, and painted metals is good. Its firmness gives it very good press runnability and very good trimming characteristics. It is not recommended for water immersion.

Type	General Purpose Removable
Classification	Emulsion Acrylic
pH	Alkaline
Minimum Application Temp., °F	20
Service Temperature Range, °F	0 to +150
Regulatory Compliances	Primary Skin Irritant 16 CFR 1500.41, FDA 21 CFR 175.105, CPSIA, RoHS, CONEG, ASTM F963 Child Toy Safety

**LINER DESCRIPTION: 6 Mil BKS**

A clay-coated kraft liner. Recommended for roll-to-sheet or roll-to-fanfold applications.

Basis Weight (25 x 38 / 500), lbs.	88.5
Caliper, mils	6.2
Gloss, 75°, %	18
Tear, MD / CD, g	90 / 108
Tensile, MD / CD, lbs.	46 / 19
Regulatory Compliances	ASTM F963 Child Toy Safety, CONEG, RoHS, CPSIA

All product specifications are for informational use only. Each customer and/or end user should determine the suitability of any product for their particular application . The above specifications are based on typical values and most current information. Specific products listed were current at the time of publication, however, all raw materials are subject to change.

Shelf Life: One year when stored at 72°F / 50% RH.