



**FACESTOCK DESCRIPTION: 3 Mil Gloss VersaPly™**

A strong, durable reinforced facestock with medium gloss and a smooth surface. It also has good opacity and brightness. 3 mil VersaPly™ also has wet strength properties for enhanced performance in moist or wet environments. End use examples include shelf marking, drum labels, horticultural tags, and beverage label applications among others. Suitable for laser printing as well as water-based and UV flexo, and UV letterpress printing.

Basis Weight (25 x 38 / 500), lbs.	62
Caliper, mils	3.1
Brightness, %	87
Gloss, 75°, %	75
Opacity, %	88

**ADHESIVE DESCRIPTION: H-311**

H-311 is a premium acrylic adhesive from Wausau Coated that advances adhesive technology by delivering the difficult-to-achieve combination of clean die-cutting with high initial tack in the most challenging conditions: Warm temperatures to refrigerator to frosty freezer conditions.

Type	Hybrid
Classification	Emulsion Acrylic
Minimum Application Temp., °F	-15
Service Temperature Range, °F	-20 to +175
Regulatory Compliances	FDA 21 CFR 175.105, REACH, RoHS, CONEG

**LINER DESCRIPTION: 80# Layflat**

Clay-coated bleached kraft liner designed for roll-to-sheet applications.

Basis Weight (25 x 38 / 500), lbs	84.5
Caliper, mils	4.6
Opacity, %	86
Tear, MD / CD, g	61 / 71
Tensile, MD / CD, psi	36 / 21
Regulatory Compliances	Acid Free, ASTM F963 Child Toy Safety, CONEG, RoHS, REACH, FDA 21 CFR 175.105

All product specifications are for informational use only. Each customer and/or end user should determine the suitability of any product for their particular application . The above specifications are based on typical values and most current information. Specific products listed were current at the time of publication, however, all raw materials are subject to change.

Shelf Life: One year when stored at 72°F / 50% RH.