

FACESTOCK DESCRIPTION: 70# Natural Felt With 30% PCW, FSC® Certified

70# Recycled Natural Felt features a distinct texture, high opacity and excellent ink holdout. This facestock also contains 30% post consumer waste content making it an excellent choice for eco-friendly applications. This sheet is also manufactured with 100% wind-generated energy and is FSC® Certified. It is manufactured with "wet strength" properties to increase performance in moist environments.



Basis Weight (25 x 38 / 500), lbs.	70
Caliper, mils	6.3
Opacity, %	93
Tear, MD / CD, g	68 / 72
Tensile, MD / CD, lbs	35 / 23
Recycled Content, %	30
PCW, %	30
Regulatory Compliances	Wind Generated Manufactured, FSC® Certified, FSC® is a voluntary program, and not legally required to be adhered to

ADHESIVE DESCRIPTION: WL-100

A cold temperature emulsion acrylic permanent, with good initial tack and short term repositionability. WL100 is an excellent performer both at room temperature and in ice bucket conditions on a variety of substrates including glass, rigid plastic, films, metals, and corrugated. Designed for beverage labels, it provides good die-cutting and stripping characteristics.

Type	Cold Temperature Permanent
Classification	Emulsion Acrylic
pH	Alkaline
Minimum Application Temp., °F	25
Service Temperature Range, °F	-10 to +200
Regulatory Compliances	Natural Rubber Latex Free, CONEG, RoHS, Acute Oral Toxicity 16 CFR 1500.3, REACH, CPSIA, Non-ozone Depleting, FDA 21 CFR 175.105, Primary Skin Irritant 16 CFR 1500.41, Primary Eye Irritant 16 CFR 1500.42, ASTM F963 Child Toy Safety

LINER DESCRIPTION: 1.2 Mil Clear Polyester

A clear polyester film liner with high strength and durability. Typically used for high speed automatic roll-to-roll applications.

Caliper, mils	1.2
Yield, sq. in/lb	16,500
Tensile Strength, MD / TD, psi	29,900 / 29,900
Haze, %	3.5%
Elongation at break, MD / TD, %	100 / 100
Shrinkage at 302°F/30 min., MD / TD, %	2 / 0.4
Regulatory Compliances	CONEG, REACH

All product specifications are for informational use only. Each customer and/or end user should determine the suitability of any product for their particular application. The above specifications are based on typical values and most current information. Specific products listed were current at the time of publication, however, all raw materials are subject to change.



Wausau Coated Products, Inc.

Product Specification W025059

70# Natural Felt With 30% PCW, FSC®

Certified / WL-100 / 1.2 Mil Clear Polyester

Shelf Life: One year when stored at 72°F / 50% RH.