

FACESTOCK DESCRIPTION: 60# High Gloss

A premium quality high gloss with a blue-white shade and mirror-smooth surface. It has a consistent finish that provides excellent ink receptivity and maximum toner anchorage. Suitable for letterpress, offset, gravure, and water and UV flexographic printing applications.

| | |
|------------------------------------|--|
| Basis Weight (25 x 38 / 500), lbs. | 57.4 |
| Caliper, mils | 3.7 |
| Brightness, % | 87 |
| Gloss, 75°, % | 90 |
| Opacity, % | 90 |
| Tear, MD / CD, g | 40 / 35 |
| Tensile, MD / CD, lbs. | 25 / 12 |
| Regulatory Compliances | California Proposition 65, CONEG, RoHS, FDA 21 CFR 176.170, REACH, CPSIA |

ADHESIVE DESCRIPTION: PCT-245

A cold temperature emulsion acrylic permanent which exhibits good initial tack and good adhesion to a variety of substrates including corrugated, rigid plastics, films, glass, and painted metal surfaces. It offers excellent die-cutting and stripping characteristics. Adhesive designed for face and back label use on glass bottles and remains affixed when immersed in an ice bucket. It also features short term repositionability on bottles and hot water removability depending on face, substrate, water

| | |
|-------------------------------|--|
| Type | Cold Temperature Permanent |
| Classification | Emulsion Acrylic |
| pH | Alkaline |
| Minimum Application Temp., °F | 25 |
| Service Temperature Range, °F | -10 to +200 |
| Regulatory Compliances | ASTM F963 Child Toy Safety, CONEG, RoHS, Acute Oral Toxicity 16 CFR 1500.3, REACH, FDA 21 CFR 175.105, Primary Skin Irritant 16 CFR 1500.41, Primary Eye Irritant 16 CFR 1500.42 |

LINER DESCRIPTION: 44# PK

A polycoated brown kraft liner with superior die-cutting and stripping properties. Designed for high-speed label dispensing and is recommended for roll-to-roll applications.

| | |
|------------------------------------|--------------------|
| Basis Weight (25 x 38 / 500), lbs. | 48# +/- 10% |
| Caliper, mils | 3.2 +/- 10% |
| Regulatory Compliances | CONEG, RoHS, REACH |

All product specifications are for informational use only. Each customer and/or end user should determine the suitability of any product for their particular application. The above specifications are based on typical values and most current information. Specific products listed were current at the time of publication, however, all raw materials are subject to change.

Shelf Life: One year when stored at 72°F / 50% RH.