



FACESTOCK DESCRIPTION: 42# Thermal Transfer

Smudgeproof coated for rapid ink dry. Extremely smooth finish with high opacity specifically designed for premium thermal transfer barcode printing. Can also be flexo printed.

Basis Weight (25 x 38 / 500), lbs.	41.8
Caliper, mils	2.8
Brightness, %	86
Opacity, %	87
Tear, MD / CD, g	42 / 42
Tensile, MD / CD, lbs.	26 / 17
Regulatory Compliances	ASTM F963 Child Toy Safety, FDA 21 CFR 176.260, FDA 21 CFR 176.210, FDA 21 CFR 176.200, FDA 21 CFR 176.180, REACH, FDA 21 CFR 176.170, RoHS, CONEG, California Proposition 65, FDA 21 CFR 176.300

ADHESIVE DESCRIPTION: PCT-241 Blockout

Cold temperature emulsion acrylic permanent with a gray blockout feature. It exhibits very high initial tack and excellent adhesion to a variety of substrates including corrugated, rigid plastics, films, glass, and painted metal substrates. It offers good die-cutting and stripping characteristics. It is not recommended for water immersion.

Type	Cold Temperature Permanent
Classification	Emulsion Acrylic
pH	Alkaline
Minimum Application Temp., °F	25
Service Temperature Range, °F	-10 to +200
Regulatory Compliances	CONEG

LINER DESCRIPTION: 40# SC

A supercalendered bleached kraft liner. Superior die-cutting and stripping properties. Recommended for roll-to-roll applications. Good back printability.

Basis Weight (25 x 38 / 500), lbs.	44.3
Caliper, mils	2.4
Gloss, 75°, %	55
Opacity, %	62
Tear, MD / CD, g	33 / 39
Tensile, MD / CD, lbs.	39 / 17
Regulatory Compliances	CONEG, RoHS, REACH, Non-ozone Depleting

All product specifications are for informational use only. Each customer and/or end user should determine the suitability of any product for their particular application. The above specifications are based on typical values and most current information. Specific products listed were current at the time of publication, however, all raw materials are subject to change.

Shelf Life: One year when stored at 72°F / 50% RH.