



FACESTOCK DESCRIPTION: 60# Matte

High opacity, high brightness facestock with a smooth consistent surface that delivers excellent print performance and ink holdout. It has a reduced gloss level and is suitable for offset and flexographic printing applications.

Basis Weight (25 x 38 / 500), lbs.	60.5
Caliper, mils	3.4
Brightness, %	91
Gloss, 75°, %	26
Opacity, %	92
Tear, MD / CD, g	46 / 52
Tensile, MD / CD, lbs.	27 / 13
Regulatory Compliances	Elemental Chlorine Free, ASTM F963 Child Toy Safety, California Proposition 65, CONEG, RoHS, REACH, CPSIA, Non-ozone Depleting, Lignin Free

ADHESIVE DESCRIPTION: PCT-241

Cold temperature emulsion acrylic permanent which exhibits high initial tack and very good adhesion to a variety of substrates including corrugated, rigid plastics, films, glass, and painted metal substrates. It offers good die-cutting and stripping characteristics. It is not recommended for water immersion.

Type	Cold Temperature Permanent
Classification	Emulsion Acrylic
pH	Alkaline
Minimum Application Temp., °F	25
Service Temperature Range, °F	-10 to +200
Regulatory Compliances	ASTM F963 Child Toy Safety, CONEG, RoHS, Acute Oral Toxicity 16 CFR 1500.3, REACH, Non-ozone Depleting, FDA 21 CFR 175.105, Primary Skin Irritant 16 CFR 1500.41, Primary Eye Irritant 16 CFR 1500.42

LINER DESCRIPTION: 40# SC

A supercalendered bleached liner. Superior die-cutting and stripping properties. Recommended for roll-to-roll applications. Good back printability.

Basis Weight (25 x 38 / 500), lbs.	42
Caliper, mils	2.5

All product specifications are for informational use only. Each customer and/or end user should determine the suitability of any product for their particular application. The above specifications are based on typical values and most current information. Specific products listed were current at the time of publication, however, all raw materials are subject to change.

Shelf Life: One year when stored at 72°F / 50% RH.