

## 60# Solar White Classic Crest® With 30% PCW, Wet Strength, FSC® Certified, Optimized For HP Indigo Presses / H-318 / 1.2 mil Clear Polyester

### **FACESTOCK DESCRIPTION: 60# Solar White Classic Crest® With 30% PCW, Wet Strength, FSC® Certified, Optimized For HP Indigo Presses**

Elegant white smooth finish with an exceptionally clean and crisp appearance. Top coated and optimized for HP Indigo Presses. It is a great stock for premium prestigious labeling such as wine bottles and home-craft labeling. This paper is also FSC® Certified and is manufactured with wet strength properties to increase performance in moist environments.



Basis Weight (25 x 38 / 500), lbs.	60
Caliper, mils	4.4
Brightness, %	91.3
Opacity, %	90
Smoothness, Sheffield, units	125
Regulatory Compliances	FSC® Certified, FSC® is a voluntary program, and not legally required to be adhered to, ASTM F963 Child Toy Safety, California Proposition 65, CONEG, RoHS

FSC® is a registered trademark of Forest Stewardship Council™.  
Classic Crest® is a registered trademark of Neenah Paper, Inc.

### **ADHESIVE DESCRIPTION: H-318**

H-318 is the ideal choice for high end beverage and spirits, with improved resistance to moisture and humidity after bottling and at presentation to the consumer. H-318 is an aggressive, blended emulsion acrylic adhesive with the unique ability to combine special characteristics from different adhesives. H-318 was engineered to provide excellent high initial tack and quicker label adhesion onto glass while providing functional converting performance on an array of paper and film face stocks.

Type	Hybrid
Classification	Emulsion Acrylic
Minimum Application Temp., °F	35
Service Temperature Range, °F	+10 to +150
Regulatory Compliances	FDA 21 CFR 175.105

### **LINER DESCRIPTION: 1.2 Mil Clear Polyester**

A clear polyester film liner with high strength and durability. Typically used for high speed automatic roll-to-roll applications.

Caliper, mils	1.2
Yield, sq. in/lb	16,500
Tensile Strength, MD / TD, psi	29,900 / 29,900
Haze, %	3.5%
Elongation at break, MD / TD, %	100 / 100
Shrinkage at 302°F/30 min., MD / TD, %	2 / 0.4
Regulatory Compliances	CONEG, REACH

All product specifications are for informational use only. Each customer and/or end user should determine the suitability of any product for their particular application. The above specifications are based on typical values and most current information. Specific products listed were current at the time of publication, however, all raw materials are subject to change.



# Wausau Coated Products, Inc.

Product Specification W029459

60# Solar White Classic Crest® With 30% PCW, Wet Strength, FSC®  
Certified, Optimized For HP Indigo Presses / H-318 / 1.2 mil Clear Polyester

---

Shelf Life: One year when stored at 72°F / 50% RH.