



**FACESTOCK DESCRIPTION: 60# Premium Matte Inkjet**

Lightweight high opacity inkjet photo and presentation paper with a matte finish and high brightness level. Universal printability on monochrome and color inkjet desktop printers. Excellent color reproduction with high dot resolution and waterfastness. Typical end uses include labels with photos. Also great for on-demand and variable information printing applications such as address labels, gourmet food labels, specialty food labels, and home-made crafts.

Basis Weight (25 x 38 / 500), lbs	59
Caliper, mils	4.52
Opacity, %	89
CIE Whiteness, units	155

Avoid exposure to ozone, exhaust fumes or solvent vapors as the absorptive nature of the print receptive topcoat could result in discoloration.

**ADHESIVE DESCRIPTION: R-2150+**

An excellent removable adhesive with low to moderate adhesion on most surfaces, R-2150+ is a good choice for a variety of removable applications. It functions most effectively on smooth surfaces, including glass, paper and painted metal. It has excellent stability and demonstrates very little growth in adhesion over time however, adhesion growth will vary depending upon substrate. Pretesting is recommended to determine end-use applicability.

Type	Ultra-Removable
Classification	Emulsion Acrylic
pH	Neutral to Slightly Alkaline
Minimum Application Temp., °F	-10
Service Temperature Range, °F	-40 to +160
Regulatory Compliances	ASTM F963 Child Toy Safety, CONEG, RoHS, Acute Oral Toxicity 16 CFR 1500.3, CPSIA, FDA 21 CFR 175.105, Primary Skin Irritant 16 CFR 1500.41, Primary Eye Irritant 16 CFR 1500.42

**LINER DESCRIPTION: 40# SC**

A supercalendered bleached liner. Superior die-cutting and stripping properties. Recommended for roll-to-roll applications. Good back printability.

Basis Weight (25 x 38 / 500), lbs.	44.7
Caliper, mils	2.5
Brightness, %	78
Gloss, 75°, %	48
Opacity, %	65
Tear, MD / CD, g	32 / 34
Tensile, MD / CD, lbs.	34 / 22
Regulatory Compliances	ASTM F963 Child Toy Safety, CONEG, RoHS, REACH

All product specifications are for informational use only. Each customer and/or end user should determine the suitability of any product for their particular application. The above specifications are based on typical values and most current information. Specific products listed were current at the time of publication, however, all raw materials are subject to change.

Shelf Life: One year when stored at 72°F / 50% RH.