

Dual Digital 70# Bright White Felt With 30% PCW, Wet Strength, FSC® Certified / Special Permanent / 80# Score Back

Sheet Size 12" x 18"

FACESTOCK DESCRIPTION: 70# Dual Digital Bright White Felt With 30% PCW, Wet Strength, FSC® Certified

Bright white premium facestock with a felt finish that provides good print integrity and color reproduction. Featuring 30% post consumer waste content making it an excellent choice for eco-friendly applications. Top coated and optimized for HP Indigo Presses as well as production toner presses. It is manufactured with "wet strength" properties to increase performance in moist environments. It is FSC® and Green Seal certified.



| | |
|------------------------------------|---|
| Basis Weight (25 x 38 / 500), lbs. | 70 |
| Caliper, mils | 6.3 |
| Brightness, % | 88 |
| Opacity, % | 93 |
| PCW, % | 30 |
| Recycled Content, % | 30 |
| Regulatory Compliances | FSC® Certified, FSC® is a voluntary program, and not legally required to be adhered to, REACH, Green Seal Certified |

ADHESIVE DESCRIPTION: Special Permanent

A cold temperature emulsion acrylic permanent which exhibits good initial tack and good adhesion to a variety of substrates. Adhesion to rigid plastics, films, glass, and painted metals is good. Cuts and die-cuts cleanly. Good choice for sheet and roll-to-sheet applications.

| | |
|-------------------------------|---|
| Type | Cold Temperature Permanent |
| Classification | Emulsion Acrylic |
| pH | Alkaline |
| Minimum Application Temp., °F | 35 |
| Service Temperature Range, °F | -10 to +200 |
| Regulatory Compliances | CONEG, RoHS, Acute Oral Toxicity 16 CFR 1500.3, REACH, FDA 21 CFR 175.105, Primary Skin Irritant 16 CFR 1500.41, Primary Eye Irritant 16 CFR 1500.42, Natural Rubber Latex Free |

LINER DESCRIPTION: 80# Score Back

Clay-coated bleached kraft liner designed for roll-to-sheet applications. Manufactured with liner scores every 1-1/4" apart.

| | |
|-----------------------------------|--|
| Basis Weight (25 x 38 / 500), lbs | 84.5 |
| Caliper, mils | 4.6 |
| Opacity, % | 86 |
| Tear, MD / CD, g | 61 / 71 |
| Tensile, MD / CD, psi | 36 / 21 |
| Regulatory Compliances | Acid Free, ASTM F963 Child Toy Safety, California Proposition 65, CONEG, RoHS, REACH, FDA 21 CFR 175.105 |

All product specifications are for informational use only. Each customer and/or end user should determine the suitability of any product for their particular application. The above specifications are based on typical values and most current information. Specific products listed were current at the time of publication, however, all raw materials are subject to change.



Wausau Coated Products, Inc.

Product Specification WCD-0005

Dual Digital 70# Bright White Felt With 30% PCW, Wet
Strength, FSC® Certified / Special Permanent / 80# Score Back

Sheet Size 12" x 18"

Shelf Life: One year when stored at 72°F / 50% RH.