



# Wausau Coated Products, Inc.

Product Specification WCD-0006

70# Eggshell Felt With 30% PCW, Wet Strength, FSC® Certified,  
Optimized For HP Indigo Presses / Special Permanent / 80# Score Back  
Sheet Size 12" x 18"

**FACESTOCK DESCRIPTION: 70# Eggshell Felt With 30% PCW, Wet Strength, FSC® Certified, Optimized For HP Indigo Presses**

70# EggShell Felt features a distinct texture, high opacity and excellent ink holdout. Top coated and optimized for HP Indigo Presses. This facestock also contains 30% post consumer waste content making it an excellent choice for eco-friendly applications. It is manufactured with wet strength properties to increase performance in moist environments. The base sheet is FSC® certified.



Basis Weight (25 x 38 / 500), lbs.	70
Caliper, mils	6.3
Opacity, %	93
Recycled Content, %	30
PCW, %	30
Regulatory Compliances	FSC® Certified, FSC® is a voluntary program, and not legally required to be adhered to, Green Seal Certified

FSC® is a registered trademark of Forest Stewardship Council™

**ADHESIVE DESCRIPTION: Special Permanent**

A cold temperature emulsion acrylic permanent which exhibits good initial tack and good adhesion to a variety of substrates. Adhesion to rigid plastics, films, glass, and painted metals is good. Cuts and die-cuts cleanly. Good choice for sheet and roll-to-sheet applications.

Type	Cold Temperature Permanent
Classification	Emulsion Acrylic
pH	Alkaline
Minimum Application Temp., °F	35
Service Temperature Range, °F	-10 to +200
Regulatory Compliances	CONEG, RoHS, Acute Oral Toxicity 16 CFR 1500.3, REACH, FDA 21 CFR 175.105, Primary Skin Irritant 16 CFR 1500.41, Primary Eye Irritant 16 CFR 1500.42, Natural Rubber Latex Free

**LINER DESCRIPTION: 80# Score Back**

Clay-coated bleached kraft liner designed for roll-to-sheet applications. Manufactured with liner scores every 1-1/4" apart.

Basis Weight (25 x 38 / 500), lbs	84.5
Caliper, mils	4.6
Opacity, %	86
Tear, MD / CD, g	61 / 71
Tensile, MD / CD, psi	36 / 21
Regulatory Compliances	Acid Free, ASTM F963 Child Toy Safety, California Proposition 65, CONEG, RoHS, REACH, FDA 21 CFR 175.105

All product specifications are for informational use only. Each customer and/or end user should determine the suitability of any product for their particular application. The above specifications are based on typical values and most current information. Specific products listed were current at the time of publication, however, all raw materials are subject to change.

Shelf Life: One year when stored at 72°F / 50% RH.