



# Wausau Coated Products, Inc.

Product Specification W032527

3.5 Mil White EVOH Laminate

## **FACESTOCK DESCRIPTION: 3.5 Mil White EVOH Laminate**

A high quality flexible packaging film that provides an excellent barrier to moisture, oxygen, and light. It also has excellent chemical resistance.

<b><i>Typical Properties</i></b>	<b><i>Typical Values</i></b>	<b><i>Units</i></b>	<b><i>Test Method</i></b>
Basis Weight (25 x 38 / 500)	62.32	lbs	ASTM D646
Caliper	3.5	mils	
Tensile Strength, MD / TD	3250 / 2900	psi	ASTM D882
Elongation MD / TD	750 / 700	%	ASTM D882
MVTR (Moisture Vapor Transmission Rate)	0.3	g/100 in <sup>2</sup> / 24 hours, 100° F / 90% R.H.	ASTM F-1249
OTR (Oxygen Transmission Rate)	0.06	cc/100 in <sup>2</sup> /24hr 23°C, 0% RH	ASTM D1434

All product specifications are for informational use only. Each customer and/or end user should determine the suitability of any product for their particular application. The above specifications are based on typical values and most current information. Specific products listed were current at the time of publication, however, all raw materials are subject to change.

Shelf Life: Six months when stored at 60-75°F / 35-55% RH.