

FACESTOCK DESCRIPTION: 60# Matte Inkjet

Lightweight high opacity inkjet photo and presentation paper with a matte finish and 94 brightness level. Universal printability on monochrome and color inkjet desktop printers. Excellent color reproduction with high dot resolution and waterfastness. Typical end uses include labels with photos. Also great for on-demand and variable information printing applications such as address labels, gourmet food labels, specialty food labels, and home-made crafts.

Basis Weight (25 x 38 / 500), lbs.	61
Caliper, mils	4.6
Brightness, %	96
Opacity, %	94
Tear, MD / CD, g	66 / 55
Tensile, MD / CD, lbs.	25 / 16
Regulatory Compliances	ASTM F963 Child Toy Safety, CONEG, RoHS, REACH, CPSIA, California Safe Drinking Water and Toxic Enforcement Act of 1986

Avoid exposure to ozone, exhaust fumes or solvent vapors as the absorptive nature of the print receptive topcoat could result in discoloration.

ADHESIVE DESCRIPTION: AT-2060

An aggressive all-temperature emulsion acrylic permanent adhesive with good room temperature and excellent cold temperature performance. Exhibits high initial tack and adhesion, even on most textured and hard-to-label substrates, including corrugated. Designed with good die-cutting and stripping properties.

Type	All-temperature Permanent
Classification	Emulsion Acrylic
pH	Neutral
Minimum Application Temp., °F	-20
Service Temperature Range, °F	-65 to +200
Regulatory Compliances	Acute Oral Toxicity 16 CFR 1500.3, ASTM F963 Child Toy Safety, California Proposition 65, CONEG, CPSIA, FDA 21 CFR 175.105, Natural Rubber Latex Free, Primary Eye Irritant 16 CFR 1500.42, Primary Skin Irritant 16 CFR 1500.41, REACH, RoHS, RoHS 2/3

LINER DESCRIPTION: 40# SC

A supercalendered bleached liner. Superior die-cutting and stripping properties. Recommended for roll-to-roll applications. Good back printability.

Basis Weight (25 x 38 / 500), lbs.	44.7
Caliper, mils	2.5
Brightness, %	78
Gloss, 75°, %	48
Opacity, %	65
Tear, MD / CD, g	32 / 34
Tensile, MD / CD, lbs.	34 / 22
Regulatory Compliances	ASTM F963 Child Toy Safety, CONEG, RoHS, REACH

All product specifications are for informational use only. Each customer and/or end user should determine the suitability of any product for their particular application. The above specifications are based on typical values and most current information.



Wausau Coated Products, Inc.

Product Specification W032301
60# Matte Inkjet / AT-2060 / 40# SC

Specific products listed were current at the time of publication, however, all raw materials are subject to change.

Shelf Life: One year when stored at 72°F / 50% RH.