



# Wausau Coated Products, Inc.

Product Specification WCD-0033

60# High Gloss Optimized For HP Indigo

Presses / Ultra-Removable / 80# Score Back

Sheet Size 12" x 18"

### **FACESTOCK DESCRIPTION: 60# High Gloss Optimized For HP Indigo Presses**

A premium quality high gloss with a mirror-smooth surface. It has a consistent finish that provides excellent ink receptivity and maximum toner anchorage. Top coated surface that is optimized for HP Indigo Presses.

Basis Weight (25 x 38 / 500), lbs.	57.4
Caliper, mils	3.7
Brightness, %	87
Gloss, 85°, %	83
Opacity, %	90
Tear, MD / CD, g	40 / 35
Tensile, MD / CD, lbs.	25 / 12
Regulatory Compliances	CONEG, RoHS

### **ADHESIVE DESCRIPTION: Ultra-Removable**

An emulsion acrylic microsphere for use in applications that require low to medium tack and clean removability. Designed for use with film facestocks for adhesion to surfaces such as painted walls and wallpaper. This adhesive may also be used with a paper facestock. Pretesting is recommended for end use applicability.

Type	Ultra-removable
Classification	Emulsion Acrylic
Minimum Application Temp., °F	20
Service Temperature Range, °F	-10 to +120
Regulatory Compliances	CONEG, RoHS, Primary Skin Irritant 16 CFR 1500.41, Primary Eye Irritant 16 CFR 1500.42

### **LINER DESCRIPTION: 80# Score Back**

Clay-coated bleached kraft liner designed for roll-to-sheet applications. Manufactured with liner scores every 1-1/4" apart.

Basis Weight (25 x 38 / 500), lbs	84.5
Caliper, mils	4.6
Opacity, %	86
Tear, MD / CD, g	61 / 71
Tensile, MD / CD, psi	36 / 21
Regulatory Compliances	Acid Free, ASTM F963 Child Toy Safety, California Proposition 65, CONEG, RoHS, REACH, FDA 21 CFR 175.105

All product specifications are for informational use only. Each customer and/or end user should determine the suitability of any product for their particular application. The above specifications are based on typical values and most current information. Specific products listed were current at the time of publication, however, all raw materials are subject to change.

Shelf Life: One year when stored at 72°F / 50% RH.