

**FACESTOCK DESCRIPTION: 60# Premium Matte Inkjet**

Lightweight high opacity inkjet photo and presentation paper with a matte finish and high brightness level. Universal printability on monochrome and color inkjet desktop printers. Excellent color reproduction with high dot resolution and waterfastness. Typical end uses include labels with photos. Also great for on-demand and variable information printing applications such as address labels, gourmet food labels, specialty food labels, and home-made crafts.

Basis Weight (25 x 38 / 500), lbs	59
Caliper, mils	4.52
Opacity, %	89
CIE Whiteness, units	155

PRODUCT DESCRIPTION: T620-U Block Out

T620-U Block Out is an ultra-aggressive permanent adhesive, a gray blockout feature. It offers excellent initial tack and ultimate adhesion to a variety of substrates, including low surface energy plastics and surfaces that come in contact with chemicals. It is UV resistant, water resistant, chemical resistant and solvent resistant.

Type	High Performance Acrylic
Classification	Acrylic
Minimum Application Temp., °F	40
Service Temperature Range, °F	-30 to +350

LINER DESCRIPTION: 40# SC

A supercalendered bleached liner. Superior die-cutting and stripping properties. Recommended for roll-to-roll applications. Good back printability.

Basis Weight (25 x 38 / 500), lbs.	44.7
Caliper, mils	2.5
Brightness, %	78
Gloss, 75°, %	48
Opacity, %	65
Tear, MD / CD, g	32 / 34
Tensile, MD / CD, lbs.	34 / 22
Regulatory Compliances	ASTM F963 Child Toy Safety, CONEG, RoHS, REACH

All product specifications are for informational use only. Each customer and/or end user should determine the suitability of any product for their particular application. The above specifications are based on typical values and most current information. Specific products listed were current at the time of publication, however, all raw materials are subject to change.

Shelf Life: One year when stored at 72°F / 50% RH.