



Wausau Coated Products, Inc.

Product Specification W033666
2.5 Mil Clear Top Coated Metalized
Polyester Laminate / T620-P / 50# SC

FACESTOCK DESCRIPTION: 2.5 Mil Clear Top Coated Metalized Polyester Laminate

A clear topcoated metalized reinforced film for laser printing applications. Engineered for superior mechanical strength, dimensional stability and optical clarity. This film provides heat and chemical resistance.

Caliper, mils	2.5
Tensile, MD / TD, psi	25,000 / 28,500
Elongation at break, MD / TD, %	125 / 90

PRODUCT DESCRIPTION: T620-P

T620-P is an ultra-aggressive permanent adhesive designed for difficult-to-label surfaces. It offers excellent initial tack and ultimate adhesion to a variety of substrates, including low surface energy plastics and surfaces that come in contact with chemicals. It is UV resistant, water resistant, chemical resistant and solvent resistant.

Type	High Performance Acrylic
Classification	Acrylic
Minimum Application Temp., °F	40
Service Temperature Range, °F	-30 to +350

LINER DESCRIPTION: 50# SC

A supercalendered bleached kraft liner. Superior die-cutting and stripping properties. Recommended for roll-to-sheet or roll-to-fanfold applications. Good back printability.

Basis Weight (25 x 38 / 500), lbs.	57.5
Caliper, mils	3.2
Brightness, %	78
Gloss, 75°, %	48
Opacity, %	75
Tear, MD / CD, g	44 / 48
Tensile, MD / CD, lbs.	43 / 27
Regulatory Compliances	ASTM F963 Child Toy Safety, CONEG, RoHS, REACH, Lignin Free

All product specifications are for informational use only. Each customer and/or end user should determine the suitability of any product for their particular application. The above specifications are based on typical values and most current information. Specific products listed were current at the time of publication, however, all raw materials are subject to change.

Shelf Life: One year when stored at 72°F / 50% RH