



FACESTOCK DESCRIPTION: 8 pt. C1S Tag

High quality medium gloss, strong tag stock with good opacity, and a smooth finish. Great where an extra stiff label is needed. Typical end uses include durable posters, signs, displays, and large labels.

Basis Weight (25 x 38 / 500), lbs.	118.7
Caliper, mils	8
Brightness, %	92
Gloss, 75°, %	51
Whiteness	122
Regulatory Compliances	ASTM F963 Child Toy Safety, California Proposition 65, CONEG, RoHS 1, REACH 1st -16th

ADHESIVE DESCRIPTION: Permanent

A cold temperature emulsion acrylic permanent which exhibits good initial tack and good adhesion to a variety of substrates. Adhesion to rigid plastics, films, glass, and painted metals is good. Cuts and die-cuts cleanly. Good choice for sheet and roll-to-sheet applications.

Type	Cold Temperature Permanent
Classification	Emulsion Acrylic
pH	Alkaline
Minimum Application Temp., °F	35
Service Temperature Range, °F	-10 to +200
Regulatory Compliances	California Proposition 65, CONEG, RoHS, Acute Oral Toxicity 16 CFR 1500.3, REACH, FDA 21 CFR 175.105, Primary Skin Irritant 16 CFR 1500.41, Primary Eye Irritant 16 CFR 1500.42

LINER DESCRIPTION: 80# Zero Split

Clay-coated bleached kraft liner designed for roll-to-sheet applications.

Basis Weight (25 x 38 / 500), lbs	84.5
Caliper, mils	4.6
Opacity, %	86
Tear, MD / CD, g	61 / 71
Tensile, MD / CD, psi	36 / 21
Regulatory Compliances	Acid Free, ASTM F963 Child Toy Safety, CONEG, RoHS, REACH, FDA 21 CFR 175.105

All product specifications are for informational use only. Each customer and/or end user should determine the suitability of any product for their particular application. The above specifications are based on typical values and most current information. Specific products listed were current at the time of publication, however, all raw materials are subject to change.

Shelf Life: One year when stored at 72°F / 50% RH.