



# Wausau Coated Products, Inc.

Product Specification DC01832

50# Premium Uncoated Laser / Inkjet / Removable / 52# Laser

8-1/2" x 11" Sheet, 6-up, Label Size 4" x 3-1/3"

### **FACESTOCK DESCRIPTION: 50# Premium Uncoated Laser / Inkjet**

Premium quality uncoated paper with high brightness and an extremely smooth surface technologically engineered for inkjet and laser printers as well as color copiers. Also suitable for flexographic and offset printing.

Basis Weight (25 x 38 / 500), lbs.	50
Caliper, mils	3.5
Brightness, %	94
Opacity, %	88
Tear, MD / CD, g	40 / 40
Tensile, MD / CD, lbs.	25 / 17
Smoothness, Sheffield, units	90
pH	Alkaline
Regulatory Compliances	ASTM F963 Child Toy Safety, California Proposition 65, CONEG, RoHS, REACH

### **ADHESIVE DESCRIPTION: Removable**

This adhesive has good initial tack and adhesion to papers. Adhesion to rigid plastics, films, glass, and painted metals is good. Its firmness gives it very good press runnability and very good trimming characteristics. It is not recommended for water immersion.

Minimum Application Temp., °F	20
Classification	Emulsion Acrylic
Type	General Purpose Removable
Service Temperature Range, °F	0 to +150
pH	Alkaline
Regulatory Compliances	ASTM F963 Child Toy Safety, CONEG, RoHS, FDA 21 CFR 175.105, Primary Skin Irritant 16 CFR 1500.41

### **LINER DESCRIPTION: 52# Laser**

A supercalendered bleached kraft liner specially designed for sheeted applications and well suited for laser printing. Features excellent dimensional stability. Recommended for roll-to-sheet applications.

Basis Weight (25 x 38 / 500), lbs.	50
Caliper, mils	3.4
Brightness, %	80
Opacity, %	82
Tear, CD, g	52
Tensile, MD, lbs.	31

All product specifications are for informational use only. Each customer and/or end user should determine the suitability of any product for their particular application. The above specifications are based on typical values and most current information. Specific products listed were current at the time of publication, however, all raw materials are subject to change.

Shelf Life: One year when stored at 72°F / 50% RH.