



# Wausau Coated Products, Inc.

Product Specification WC1200

60# High Gloss Laser / Color

Copier / Permanent / 52# Score Back

Sheet Size 8-1/2 x 11

### **FACESTOCK DESCRIPTION: 60# High Gloss Laser / Color Copier**

A premium quality high gloss with a blue-white shade and mirror-smooth surface. It has a consistent finish that provides excellent ink receptivity and maximum toner anchorage. Suitable for letterpress, offset, gravure, and water and UV flexographic printing applications.

Opacity, %	90
Brightness, %	87
Caliper, mils	3.7
Tensile, MD / CD, lbs.	25 / 12
Tear, MD / CD, g	40 / 35
Basis Weight (25 x 38 / 500), lbs.	57.4
Regulatory Compliances	California Proposition 65, CONEG, RoHS, FDA 21 CFR 176.170, REACH, CPSIA

### **ADHESIVE DESCRIPTION: Permanent**

A cold temperature emulsion acrylic permanent which exhibits good initial tack to a variety of substrates. Adhesion to rigid plastics, film, glass, and painted metals is good. Die-cuts cleanly. Designed for laser applications and is a good choice for roll-to-sheet applications.

Classification	Emulsion Acrylic
Service Temperature Range, °F	-10 to +200
Minimum Application Temp., °F	35
pH	Alkaline
Type	Cold Temperature Permanent
Regulatory Compliances	California Proposition 65, CONEG, RoHS, Acute Oral Toxicity 16 CFR 1500.3, REACH, FDA 21 CFR 175.105, Primary Skin Irritant 16 CFR 1500.41, Primary Eye Irritant 16 CFR 1500.42

### **LINER DESCRIPTION: 52# Score Back**

A supercalendered bleached kraft liner. Superior die-cutting and stripping properties. Manufactured with liner scores every 1-1/4" apart.

Tensile, MD / CD, lbs.	43 / 27
Basis Weight (25 x 38 / 500), lbs.	57.5
Tear, MD / CD, g	44 / 48
Opacity, %	75
Gloss, 75°, %	48
Brightness, %	78
Caliper, mils	3.2
Regulatory Compliances	ASTM F963 Child Toy Safety, CONEG, RoHS, REACH

All product specifications are for informational use only. Each customer and/or end user should determine the suitability of any product for their particular application. The above specifications are based on typical values and most current information. Specific products listed were current at the time of publication, however, all raw materials are subject to change.

Shelf Life: One year when stored at 72°F / 50% RH.