



Wausau Coated Products, Inc.

Product Specification QS9905

3.4 mil TC White Flexible Vinyl

/ Ultra-Removable / 80# Zero Split

27" Net Width

FACESTOCK DESCRIPTION: 3.4 Mil TC White Flexible Vinyl

A smooth finish vinyl film with a matte top coat suitable for offset and flexographic printing applications. High durability and moisture resistant; also has good chemical resistance. Top coat also impedes plasticizer migration. Special inks are required and testing is recommended.

Caliper, mils	3.4
Yield, sq. in/lb	5,576
Brightness, %	87.4
Tensile Strength, MD / CD, psi	3800 / 3350
Elongation Rate, MD / CD, %	120 / 242
Regulatory Compliances	ASTM F963 Child Toy Safety, CONEG, RoHS, REACH

ADHESIVE DESCRIPTION: Ultra-Removable

An emulsion acrylic ultra-removable adhesive with low tack on flat smooth surfaces. It can be cleanly removed after an extended period of time. Applications include glass, counter tops, painted metal, smooth painted walls, and stainless steel. For optimum performance, we recommend a film facestock. This ultra-removable adhesive has demonstrated good cold temperature properties under certain conditions. Qualifying the adhesive for the specific end-use substrate is a prerequisite.

Type	Ultra-Removable
Classification	Emulsion Acrylic
pH	Alkaline
Minimum Application Temp., °F	-15
Service Temperature Range, °F	-60 to +160
Regulatory Compliances	Natural Rubber Latex Free, FDA 21 CFR 175.105, RoHS, CONEG, ASTM F963 Child Toy Safety

LINER DESCRIPTION: 80# Score Back

Clay-coated bleached kraft liner designed for roll-to-sheet applications. Manufactured with liner scores every 1-1/4" apart.

Basis Weight (25 x 38 / 500), lbs.	80
Caliper, mils	4.6
Brightness, %	78
Gloss, 75°, %	25
Opacity, %	84
Tear, MD / CD, g	70 x 70
Tensile, MD / CD, n/in	220 / 100
Regulatory Compliances	ASTM F963 Child Toy Safety, CONEG, RoHS, REACH, FDA 21 CFR 175.105

All product specifications are for informational use only. Each customer and/or end user should determine the suitability of any product for their particular application. The above specifications are based on typical values and most current information. Specific products listed were current at the time of publication, however, all raw materials are subject to change.

Shelf Life: One year when stored at 72°F / 50% RH.