



Wausau Coated Products, Inc.

Product Specification W019985

5 mil White Matte Kimdura® Inkjet / SW-95 / 50# SC

BS 5609 Certified

FACESTOCK DESCRIPTION: 5 mil White Matte Kimdura® Inkjet

This face sheet is specifically engineered to perform in inkjet printing applications. In addition, it is writable with pen, pencil, surgical marker, and Sharpie markers. Provides excellent resistance to chemicals and moisture in harsh environments.

Basis Weight (25 x 38 / 500), lbs	76.2
Caliper, mils	5.1
Gloss, 75°, %	4
Sheffield Smoothness, mL/min	50
Regulatory Compliances	REACH

®Kimdura is a registered trademark of Neenah Paper Inc.

ADHESIVE DESCRIPTION: SW-95

A general purpose permanent emulsion acrylic adhesive that provides aggressive adhesion to a variety of surfaces including metal drums, poly drums, and corrugated drums.

Type	Permanent
Classification	Emulsion Acrylic
pH	Alkaline
Minimum Application Temp., °F	20
Service Temperature Range, °F	-30° - 190
Regulatory Compliances	British Standard - BS 5609

*SW-95 complies with all of the requirements of the British Saltwater Immersion Test (BS 5609) when used with Wausau Coated Products' 5 mil White Matte Inkjet Synthetic Drum Label facestocks on Epson Inkjet Printers (TM-C3400, GP-C820, C830 and B-510).

LINER DESCRIPTION: 50# SC

A supercalendered bleached kraft liner. Superior die-cutting and stripping properties. Recommended for roll-to-sheet or roll-to-fanfold applications. Good back printability.

Basis Weight (25 x 38 / 500), lbs.	57.5
Caliper, mils	3.2
Brightness, %	78
Gloss, 75°, %	48
Opacity, %	75
Tear, MD / CD, g	44 / 48
Tensile, MD / CD, lbs.	43 / 27
Regulatory Compliances	ASTM F963 Child Toy Safety, CONEG, RoHS, REACH

All product specifications are for informational use only. Each customer and/or end user should determine the suitability of any product for their particular application. The above specifications are based on typical values and most current information. Specific products listed were current at the time of publication, however, all raw materials are subject to change.

Shelf Life: One year when stored at 72°F / 50% RH.