



FACESTOCK DESCRIPTION: 2.6 Mil White Polypropylene Optimized For HP Indigo Presses

A white polypropylene film top coated and optimized for HP Indigo Presses. It is very durable with high opacity and is biaxially oriented with good stiffness for conversion and automatic label dispensing.

Caliper, mils	2.6
Yield, sq. in/lb	15,000
Opacity, %	88
Tensile Strength, MD / TD, psi	13,100 / 27,700
Tensile Elongation, MD / TD, %	200 / 50
Stiffness, Gurley, MD / TD, mg	22 / 42
Dimensional Stability, MD / TD, %	-5.0 / -5.0
Regulatory Compliances	California Proposition 65, RoHS, REACH, Dodd-Frank Legislation, Lead Free

ADHESIVE DESCRIPTION: i8308

i8308 is an ultra-aggressive permanent designed for difficult-to-label surfaces. It offers excellent initial tack and ultimate adhesion to a variety of substrates. i8308 is UV resistant, water resistant, and offers some solvent resistance.

Type	High Performance Acrylic
Classification	Acrylic
pH	Slightly Acidic
Minimum Application Temp., °F	+20
Service Temperature Range, °F	-20 to +300
Regulatory Compliances	California Proposition 65, CONEG, Natural Rubber Latex Free, Primary Skin Irritant 16 CFR 1500.41, REACH, RoHS, FDA 21 CFR 175.105, FDA 21 CFR 175.125 Table 2 D-G, FDA 21 CFR 176.180

LINER DESCRIPTION: 40# SC

A supercalendered bleached liner. Superior die-cutting and stripping properties. Recommended for roll-to-roll applications. Good back printability.

Basis Weight (25 x 38 / 500), lbs.	42
Caliper, mils	2.5

All product specifications are for informational use only. Each customer and/or end user should determine the suitability of any product for their particular application. The above specifications are based on typical values and most current information. Specific products listed were current at the time of publication, however, all raw materials are subject to change.

Shelf Life: One year when stored at 72°F / 50% RH.