



FACESTOCK DESCRIPTION: 60# Semi Gloss Optimized For HP Indigo Presses

High quality, high brightness, highly opaque, semi gloss facestock with excellent gloss level. Top coated and optimized for HP Indigo Presses. Base sheet contains archival properties, is elemental chlorine free and lignin free. It features excellent ink anchorage and high strength for die cutting and matrix stripping.

Basis Weight (25 x 38 / 500), lbs.	60
Caliper, mils	3
Brightness, %	90
Opacity, %	91
Tear, MD / CD, g	30 / 30
Tensile, MD / CD, lbs.	35 / 17
Regulatory Compliances	ASTM F963 Child Toy Safety, California Proposition 65, CONEG, RoHS

ADHESIVE DESCRIPTION: PCT-524

A very aggressive cold temperature permanent adhesive with great cold flow properties and an excellent choice for dairy label applications. PCT-524 will adhere to a frosted surface depending on the amount of frost and moisture present. Pretesting to determine end use applicability is recommended.

Type	Cold Temperature Permanent
Classification	Rubber Based
Minimum Application Temp., °F	10
Service Temperature Range, °F	-40 to +150
Regulatory Compliances	CONEG, RoHS, REACH, FDA 21 CFR 175.105, Natural Rubber Latex Free

LINER DESCRIPTION: 40# SC

A supercalendered bleached liner. Superior die-cutting and stripping properties. Recommended for roll-to-roll applications. Good back printability.

Basis Weight (25 x 38 / 500), lbs.	42
Caliper, mils	2.5

All product specifications are for informational use only. Each customer and/or end user should determine the suitability of any product for their particular application. The above specifications are based on typical values and most current information. Specific products listed were current at the time of publication, however, all raw materials are subject to change.

Shelf Life: One year when stored at 72°F / 50% RH.